

IR-860 ENERGY MODULATOR SYSTEM



Specifications:

- Motor Spindle Speed Range:** 75-7500 RPM
- Warm Up Time:** 1 Hour for Optimum Stability
- Stability:** 0.5% of set frequency or 0.25% of full scale over 4 hours
- Control Type:** Closed Loop Brushless DC Motor Controller with Phase Sensors
- Meter Indication:** Chopping Frequency in Hertz
- Meter Accuracy:** ± 1 Digit
- Reference Frequency Output:** 0-5 V TTL Level, 600 Ohms Output
- Power Requirements:** 200 Watts 110 or 220 VAC 50-60 Hz
- Dimensions: Modulator:** 6.88" Diameter (175mm)
- Controller:** 8.5" x 8" x 3.75" (216x203x95mm)
- Weight:** 6.5 lbs

Interfaces directly with the IR-563 and IR-564 Blackbody Systems

BLADE TYPES:

Blade	Freq Range	Number of Slots	Slot Width @ Center	Maximum Aperture
A	1.25-125HZ	1	7.854"	1.0"
B	2.5-250HZ	2	3.927	1.0
C	10-1000HZ	8	0.982	0.992
<i>STANDARD BLADE</i>				
D	30-3000HZ	24	0.327	0.327
E	50-5000HZ	40	0.196	0.196
F	100-10000HZ	80	0.098	0.098
G	300-30000HZ	240	0.0327	0.0327
H	62.5-6250HZ	50	0.157	0.157
J	450-45000HZ	360	0.022	0.022
K	3.75-375HZ	3	2.618	1.0

7319 SANDSCOVE CT. #4 Φ WINTER PARK, FL 32792

(TEL) 407-679-5101 Φ (FAX) 407-679-5520

SALES@INFRAREDSYSTEMS.COM [HTTP://WWW.INFRAREDSYSTEMS.COM](http://WWW.INFRAREDSYSTEMS.COM)

IR-762 ENERGY MODULATOR SYSTEM



SPECIFICATIONS:

- Dimensions:** 5.8"W x 2.8"H x 12.5"D
- Input and Output Connectors:** BNC's
- Frequency Control:** Up/Down Keypad Switches
- Mode Control:** Keypad Switch Enable with LED Illuminated Selection
- External Control:** Keypad Switch Enable with LED Indication
- Input Power Connection:** IEC Connector with US style power cord
- Weight:** 5lbs (10 lbs. Shipped weight)
- Operating Temp:** 10-40° C
- Display Type:** Green LED Segments
- No of Digits:** 4
- Frequency Resolution:** 1 HZ

762 HEAD

- Motor:** 11 pole dc motor, sleeve bearing, precious metal bushes
- Ambient Temp:** -20°C to + 65°C
- Optical Sensor:** High speed, IR LED Phototransistor Switch
- Finish:** Non-reflective Mil-A-8625E Type II black anodized

POWER SUPPLY

- Supply Type:** Linear
- Voltage Selection:** 115 / 230 VAC
- Input Voltage:** 110 / 115 VAC +/- 10%, 230VAC +/- 10%
- Line Frequency:** 50-60Hz
- Input Power:** 20VA MAX
- Fuse Ratings:** 250mA @ 115VAC
125mA @ 230VAC
- Fuse Type:** IEC60127-2/III (250V, Slow Blow Type 'T')

BLADE TYPES:

Freq Range	Number of Slots	Maximum Aperture	Jitter
20 Hz – 200 Hz	2	1.85"	+/- 0.2° max
<i>STANDARD BLADE</i>			
20 Hz – 1 KHz	10	0.40"	+/- 1° max
60 Hz – 3 KHz	30	0.13"	+/- 3° max

7319 SANDSCOVE CT. #4 ☐ WINTER PARK, FL 32792
(TEL) 407-679-5101 ☐ (FAX) 407-679-5520

SALES@INFRAREDSYSTEMS.COM [HTTP://WWW.INFRAREDSYSTEMS.COM](http://WWW.INFRAREDSYSTEMS.COM)